

7150型クローラクレーン 定格総荷重表  
[非自航式台船搭載]

■主ブーム定格総荷重表 (ton) / 標準カウンタウエイト54ton付

(単位:t)

作業半径(m) \ ブーム長さ(m)	18.29	21.34	24.38	27.43	30.48	33.53	36.58	39.62	42.67	45.72	48.77	51.82
5.0	91.0											
6.0	91.0	91.0	91.0									
7.0	91.0	91.0	91.0	91.0	94.4							
8.0	91.0	91.0	91.0	91.0	90.7	83.8	77.8					
9.0	82.5	82.3	82.2	82.0	81.8	78.8	75.2	69.6				
10.0	70.5	70.3	70.2	70.1	69.9	69.8	69.2	66.5	62.3	57.8		
12.0	54.6	54.3	54.2	54.0	53.8	53.7	53.5	53.3	53.2	52.2	49.6	46.9
14.0	44.5	44.2	44.0	43.9	43.6	43.5	43.2	43.1	42.9	42.7	42.6	41.8
16.0	37.5	37.1	37.0	36.8	36.5	36.4	36.1	35.9	35.8	35.6	35.5	35.2
18.0		32.0	31.8	31.6	31.3	31.1	30.8	30.7	30.6	30.4	30.2	30.0
20.0			27.8	27.6	27.3	27.1	26.8	26.7	26.5	26.3	26.2	25.9
22.0			24.7	24.4	24.2	24.0	23.7	23.5	23.4	23.1	23.0	22.8
24.0				21.9	21.6	21.4	21.1	20.9	20.8	20.6	20.4	20.2
26.0					19.5	19.3	19.0	18.8	18.7	18.4	18.2	18.0
28.0						17.5	17.2	17.0	16.9	16.6	16.4	16.2
30.0						16.1	15.7	15.5	15.4	15.1	14.9	14.7
32.0							14.4	14.2	14.0	13.8	13.6	13.4
34.0								13.1	12.9	12.7	12.5	12.2
36.0									11.9	11.7	11.5	11.2
38.0									11.1	10.8	10.6	10.3
40.0										10.1	9.8	9.6
42.0											9.1	8.9
44.0												8.2
46.0												7.7

<注>

- ① 定格総荷重は、フックブロック、玉掛用ワイヤロープ等のつり具の質量を含んだ値です。
- ② 上表能力は本機を台船に搭載し台車を固縛した時の能力です。